



Cat® 426F2

BACKHOE LOADER

FEATURES:

- **Product Link™** – Get the most out of your Cat® Backhoe Loader. Product Link provides quick access to vital information such as machine location, hours worked, machine error codes and fuel burn to help you maximize machine performance.
- **Cab and Controls** – The introduction of the new cab to the Cat Backhoe Loader provides a comfortable and easy to use operator environment. With the ability to customize your experience, the all new cab allows the operator to perform in greater comfort and enjoy the latest technologies available on today's generation of backhoe loaders.

- **Powerful Hydraulics** – The F2 Series machines really make an impact. High pump flow in a superior hydraulic system allow the operator excellent hydraulic performance at their fingertips.
- **Power Train** – The 426F2 is equipped with our tried and tested Cat 3054C engine and is finely tuned to a Cat four speed manual transmission. This fine tuning enables the 426F2 to reach a 40 km/h roading speed.

Specifications

Engine

Model	Cat 3054C Mechanical Turbo
Rated Power (standard) @ 2,200 rpm	
Gross Power ISO 14396	68.5 kW/93 hp
Net Power Rating @ 2,200 rpm ISO 9249	66 kW/88 hp
Net Peak Power @ 2,000 rpm SAE J1349	65 kW/87 hp
ISO 9249	65 kW/88 hp
EEC 80/1269	65 kW/88 hp
Torque Rise (net) @ 1,200 rpm	38%
Maximum Torque @ 1,400 rpm	394 N·m
Bore	105 mm
Stroke	127 mm
Displacement	4.4 L

- Net power advertised is the power available at the flywheel when the engine is equipped with fan, air cleaner, muffler and alternator.
- No derating required up to 2286 m altitude. Auto derate protects hydraulic and transmission systems.
- Engine meets U.S. EPA Tier 2/EU Stage II equivalent emission standards.

Hydraulic System

Type	Closed Center
Pump Type	Variable Flow, Axial Piston
Maximum Pump Capacity	132 L/min
System Pressure	
Backhoe	250 Bar
Loader	250 Bar

Noise Level

Inside Cab	80 dB(A)
Outside Cab	104 dB(A)

Transmission

Travel speeds of Two Wheel Drive backhoe loader at full throttle, when equipped with 16.9x28 rear tires.

Power Shuttle		Power Shuttle	
Forward		Reverse	
1st	5.5 km/h	1st	5.5 km/h
2nd	9.0 km/h	2nd	9.0 km/h
3rd	20.7 km/h	3rd	20.7 km/h
4th	40.0 km/h	4th	40.0 km/h

Service Refill Capacities

Cooling System	22.0 L
Fuel Tank	160 L
Engine Oil with Filter	8.8 L
Transmission (Power Shuttle)	
AWD	15 L
Rear Axle	14.5 L
Planetaries	1.5 L
Front Axle (AWD)	11 L
Planetaries	0.7 L
Hydraulic System	106 L
Hydraulic Tank	40 L

2

Machine Dimensions

	GP – 1.05 m ³	MP – 0.96 m ³
1 Overall Length in Rooding Position	5726 mm	5682 mm
Overall Transportation Length	5678 mm	5675 mm
2 Overall Transportation Height – 4.3 m	3757 mm	3757 mm
Overall Width (excluding loader bucket)	2346 mm	2346 mm
3 Height to Top of Cab/Canopy	2869 mm	2869 mm
4 Height to Top of Exhaust Stack	2716 mm	2716 mm
5 Rear Axle Centerline to Front Grill	2708 mm	2708 mm
6 Wheelbase AWD	2200 mm	2200 mm

Dimensions and performance specifications shown are for machines equipped with 12.5/80-18 SGL front tires, 16.9-28c rear tires, standard cab, standard stick with 610 mm standard duty bucket, and 1.05 m³ GP loader bucket and standard equipment unless otherwise specified.

Loader Bucket Dimensions and Performance

	GP – 1.05 m ³	MP – 0.96 m ³
Capacity	1.05 m ³	0.96 m ³
Width	2262 mm	2262 mm
Lift Capacity at Maximum Height	3610 kg	3475 kg
Lift Breakout Force	54.46 kN	54.0 kN
Tilt Breakout Force	53.92 kN	60.48 kN
Tipping Load at Breakout Point	7012 kg	7110 kg
7 Maximum Hinge Pin Height	3447 mm	3447 mm
8 Dump Angle at Full Height	46°	46°
Dump Height at Maximum Angle	2733 mm	2764 mm
9 Dump Reach at Maximum Angle	900 mm	825 mm
10 Maximum Bucket Rollback at Ground Level	38°	39°
11 Digging Depth	88 mm	147 mm
Maximum Grading Angle	113°	116°
12 Grill to Bucket Cutting Edge, Carry Position	1482 mm	1450 mm
13 Maximum Operating Height	4368 mm	4368 mm
Bucket Weight (excluding teeth and forks)	428 kg	611 kg

Backhoe Dimensions and Performance

	Standard Stick – 4.3 m
14 Digging Depth, SAE Maximum	4119 mm
Digging Depth, Manufacturer's Maximum	4709 mm
15 Digging Depth, 2440 mm Flat Bottom	3743 mm
Digging Depth, 600 mm Flat Bottom	4094 mm
Digging Depth, 600 mm Flat Bottom, Manufacturer's	4670 mm
16 Reach from Swing Pivot at Ground Line	5609 mm
Maximum Operating Height	5719 mm
Loading Height	4031 mm
17 Loading Reach	1477 mm
Swing Arc	180°
Bucket Rotation	205°
18 Stabilizer Overall Width	2242 mm
Bucket Dig Force	57.22 kN
Stick Dig Force	35.29 kN

426F2 Backhoe Loader

Standard and Optional Equipment *(Standard and Optional equipment may vary. Consult your Cat dealer for details.)*

	Standard	Optional		Standard	Optional
Cab ROPS and FOPS			Guards		
Canopy	✓	—	Guard, Driveshaft	—	✓
Cab, Standard	—	✓	Loader Safety Brace	✓	—
Tires/Steering/Brakes			Boom, Sticks and Linkages – Backhoe		
Two Wheel Drive	✓	—	Stick, Standard (4.26 m)	✓	—
All Wheel Drive	—	✓	Transport Lock, Swing	✓	—
100% Differential Lock	✓	—	Transport Lock, Boom	✓	—
Hydraulic Boosted Brakes (dual pedals)	✓	—	Hydraulics		
Tires 16 inch (Front) – 2WD	✓	—	Hydraulic Pump (132 L/min)	✓	—
Tires 18 inch (Front) – AWD	✓	—	Side Shift Lock (electro-hydraulic)	✓	—
Tires 28 inch (Rear)	✓	—	Hydraulic Oil Cooler	✓	—
Engine/Transmission			Hydraulics – Backhoe		
Battery 750 CCA, Maintenance Free (standard)	✓	—	Hydraulic Lines, 1-Way	—	✓
Hinged Radiator Unit for Simple Debris Removal	✓	—	Hydraulic Quick Disconnects (twist to connect)	—	✓
Engine 68.5 kW (93 hp) Cat 3054C	✓	—	Hydraulics – Loader		
Transmission, 4-Speed Manual	✓	—	Loader Kickout, Float	✓	—
Input			Parallel Lift	✓	—
Controls, Mechanical Lever	✓	—	Electrical		
Power Steering, Hydrostatic	✓	—	Product Link, Cellular	✓	—
Other Attachments			Reversing Alarm	✓	—
Counterweight, 115 kg	—	✓	Beacon, Rotating	—	✓
Counterweight, 240 kg	—	✓			
Tool Storage Box	✓	—			
Transport Tie-downs	✓	—			

For more complete information on Cat products, dealer services, and industry solutions, visit us on the web at www.cat.com

© 2018 Caterpillar
All rights reserved

Materials and specifications are subject to change without notice. Featured machines in photos may include additional equipment. See your Cat dealer for available options.

CAT, CATERPILLAR, SAFETY.CAT.COM, their respective logos, “Caterpillar Yellow” and the “Power Edge” trade dress, as well as corporate and product identity used herein, are trademarks of Caterpillar and may not be used without permission.

AEHQ8016-02 (01-2018)
Replaces AEHQ8016-01
(Africa, APD, Middle East,
South America)

